

SpotOn®

SPRAYER CALIBRATOR

ACCURATE FLOW RATE MEASUREMENT IN SECONDS

SPECIFICATIONS | SC-1

Best for flow rates below 1 gpm typical of herbicide and insecticide application

Range & Units: 0.02 – 1.00 gpm (0.08 – 3.80 lpm)

Accuracy: +/- 2.5%

Size: 2.25in Dia. x 9.25in H (5.7cm Dia. x 23.5cm H)

Weight: 0.52 lb (236 g)

SPECIFICATIONS | SC-4

Best for higher flow rates between 1-4 gpm typical of liquid fertilizer application

Range & Units: 0.07 – 4.00 gpm (0.27 – 15.0 lpm)

Accuracy: +/- 4%

Size: 4in Dia. x 10in H (10.2cm Dia. x 25.4cm H)

Weight: 1.2 lb (544 g)

Every unit is hand calibrated and verified with water to assure top accuracy in the field.



FEATURES

- Quickly find worn spray nozzle tips
Industry guidelines recommend tip replacement once flow rate exceeds that of a new tip by 10%
- Accurately measure true tip flow rate
Today's high tech sprayers can only be properly calibrated and confirmed with this knowledge
- Fast and simple operation
Readings in 10 seconds or less per tip
- Displays in gpm, lpm or oz/min
- JKI - Julius Kuhn-Institut Certified G 2050

Featured in the Journal of Pesticide Safety Education
The SpotOn® Sprayer Calibrator, a Digital Flow Meter:
Accuracy Evaluation and Use in Pesticide Safety
Education Programs



Visit us at www.innoquestinc.com for complete details.

YOUTUBE.COM



SEE THE DEMO VIDEO, SEARCH
SpotOn Sprayer Calibrator

Sprayer Calibrator SC-1 • Item #: 23890 • One year warranty • Made in USA

Sprayer Calibrator SC-4 • Item #: 24200 • One year warranty • Made in USA

innoquest
Inc.

910 Hobe Road, Woodstock, IL 60098 • Phone: 815.337.8555 • Fax: 815.337.8556 • www.innoquestinc.com

© 2018 Innoquest, Inc. - USA P/N 27070 Rev. 6